

2009 JAMIS XENITH T2

UPGRADES FROM 2008

- New XS size with 650c wheels
- Refined down tube shape improving aerodynamics
- 1 1/8" head tube and steerer
- New rear brake mounting
- SRAM RED drivetrain and Carbon TT shifters
- Zipp 808/404 clincher wheels
- Zipp Vuka bar w/integrated brake levers
- Profile Design Tri-Stryke Elite saddle with titanium rails
- Ritchey Logic Pro Drop-In headset

REASONS TO UPGRADE FROM XENITH T1

- Zipp 808/404 Clincher wheels
- Vittoria Open Corsa EVO KS/EVO CX open clincher tires
- Zipp Vuka bar w/integrated brake levers
- FSA Neo Pro TT crankset
- SRAM Red Group with Carbon shifters

FEATURES/BENEFITS

Xenith T2 features full carbon fiber construction using NACA guidelines for aero profiles, San Diego Low-Speed Wind Tunnel tested, with the rear brake tucked under the chain stay for a cleaner air flow; internal cables for smooth, clean aero lines: a wheel cut-out in the seat tube to shield the rear wheel from the wind; and an aero- clean seat post/seat tube juncture with aero seat stays

Our patent pending, full carbon monocoquen WindShield® fork encloses the front brake within the fork blades for superior aerodynamics, with easy-access brake ports to simplify maintenance

The T2's aero seatpost offers two seat clamp positions so you can set & micro-adjust the saddle in a Triathlon forward position or a TT setback, road position

Zipp's 808/404 clincher wheelset features 81mm deep carbon tubular rims with aerodynamic dimples, Sapim CX-ray aero spokes (18F/24R) & Zipp 82/182 hubs: all for blazing fast speed

Vittoria's Open Corsa EVO KS/CX open clincher tires offer the lowest rolling resistance and the best ride available

FSA's Neo Pro TT crankset features hollow carbon aero crank arms with a solid aero TT chainring and a recess on the back of the crank to shroud the crankset bearings for cleaner air flow

Zipp's Vuka aero bar with Chicane extensions and integrated brake levers is not only absolutely aero it is extraordinarily adjustable

SRAM's RED group is the new standard in performance and light weight on the road

SRAM's 10-speed chain with PowerLock connecting link delivers optimal chain security and dependability with superior performance

Profile's Design Tri-Stryke Elite saddle with lightweight titanium rails offers a padded nose for comfort while in the most efficient aero position

A full range of sizes including an XS size with 650c 404 wheels



Sterling Silver/Carbon

SPECIFICATIONS

Frame	Full hi-modulus carbon Tri/TT frame, NACA compliant profiles, chainstay-mounted rear brake, internal cable routing, seat tube wheel cut-out, flat-oval top tube, aerofoil seatstays, rear-entry horizontal dropouts with axle-position adjustment bolts
Fork	Windshield aero full carbon (patent pending) with rear-facing/ enclosed front brake for reduced aerodynamic drag, with brake pad adjustment ports
Headset	Ritchey Logic Pro Drop-in, 1 1/8"
Wheels	Zipp 808 clincher wheelset (Zipp 404 650c for XS), 81mm dimpled full carbon rim, 18/24, Zipp 82/182 hubset, Sapim CX-ray spokes
Tires	Vittoria Open Corsa KS, 700 x 23c clincher (Corsa Evo CX 650 x 20c for XS)
Derailleurs	SRAM Red rear with Red braze-on front
Shiftlevers	SRAM 900 carbon TT shift levers, 20-speed
Chain	SRAM PC-1090 with PowerLock
Cassette	SRAM RED, OG-1090, 10-speed, 11-23
Crankset	FSA Neo Pro TT hollow carbon, 54/42T 170mm (XS,S) 172.5mm (M) 175mm (L, XL)
BB Set	FSA MegaExo, external with ceramic bearings
Pedals	NA
Brakeset	TRP T725 aero TT brake with Kool Stop dual compound, Zipp Vuka TT levers
Handlebar	Zipp Vuka Aero Bar, full carbon, fully adjustable with integrated brake levers
Stem	Easton EA90, 6° x 90mm (S, M), 100mm (L, XL)
Grips	Jamis gel tape
Seat Post	Jamis Aero carbon post with dual setback
Saddle	Profile design Tri-Stryke Elite with Titanium rails
Sizes	XS (650c), S, M, L, XL
Color	Sterling Silver/Carbon
Weight	18.50 lbs

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	STACK	REACH	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
XS 47 (650c)	18.19/462	19.09/485	72°	78°	18.15/461	15.24/387	14.37/365	36.14/918	1.69/43	10.11/257	3.94/100	27.64/718
S	19.88/505	20.08/510	71°	78°	19.53/496	15.95/405	15.35/390	38.54/979	1.89/48	10.63/270	3.94/100	29.80/757
M	20.27/515	20.67/525	72°	78°	20.04/509	16.42/417	15.35/390	38.54/979	1.89/48	10.63/270	4.33/110	30.31/770
M/L	21.02/534	21.45/545	72°	78°	20.91/531	17.01/432	15.35/390	38.54/979	1.89/48	10.63/270	5.31/135	31.26/794
L	22.24/565	22.64/575	72°	78°	21.89/556	17.99/457	15.35/390	38.54/979	1.89/48	10.63/270	6.30/160	32.20/818