

2009 JAMIS VENTURA COMP

UPGRADES FROM 2008

New 41cm size for younger riders featuring 650c wheels

REASONS TO UPGRADE FROM VENTURA SPORT

Lightweight double-butted 7005 frame

Full carbon composite fork

Integrated headset bearings

Alex AKX R1.0 wheelset

Shimano Tiagra/Sora 18-speed drivetrain

Easton seatpost, handlebar and stem

Selle San Marco ischia saddle



Team Red

FEATURES/BENEFITS

The Ventura frame features Size Specific Tubing (SST): smaller frames are constructed with smaller diameter tubing to retain resiliency and ride quality, while larger frames are constructed using larger diameter tubing to retain stiffness for larger riders

This frame is a competition inspired sloping top tube design featuring 7005 double-butted tubing, integrated head tube for aerodynamic efficiency & ride-tuned rear stays with replaceable RD hanger

Ventura Comp's fork features straight, aero-shaped blades and FULL carbon composite construction, including steerer and crown, for reduced weight & aerodynamic drag.

Low spoke count Alex wheels offer less aerodynamic drag than higher spoke count wheels and are lighter, reducing rotational weight for higher performance at lower energy output

FSA's compact crankset concept is revolutionary: a 34T inner chainring offers a 15% lower gear ratio than the traditional 39T double ring'd road cranks, but the 50T outer loses only 6% off the top end compared to the 53T traditional outer. You get the hill climbing capability of a triple, yet less weight than a standard double

A sealed cartridge bottom bracket improves performance and reduces maintenance

Tektro's dual pivot brakes offer safe, secure braking and high quality forged alloy construction

Shimano's Tiagra/Sora 18-speed drivetrain assures light, precise shifting throughout the entire gear range

Vittoria's Zaffiro 23c tires offer legendary, road-holding capability and superior ride quality

Selle San Marco's Ischia saddle rides comfortably & efficiently with classic Italian styling

Easton is arguably the global leader in aluminum. Their EA30 over-sized 31.8 handlebar/stem and 27.2 seatpost deliver comfort, light weight, and reliability at the rider's critical contact points

Our new 41cm version features 650c wheels with reach-adjustable Shimano brake levers, a youth specific saddle and other small-size appropriate components to make Ventura Comp a perfectly affordable high-performance dropped-bar bike for the youngster looking to get into the healthy, exciting world of road riding

SPECIFICATIONS

Frame	Kinesis 7005 double-butted main frame, SST tubing diameters, sloping top tube frame design, replaceable derailleur hanger
Fork	Full carbon composite straight blade road fork, forged alloy dropouts
Headset	Integrated, threadless, 1 1/8"
Wheels	Alex AKX R1.0 wheelset, aero profile rims with CNC sidewalls, 28/32H, radial front, 2X rear (650c size for 41cm)
Tires	Vittoria Zaffiro, 700 x 23c
Derailleurs	Shimano Tiagra rear & Sora front, 31.8mm clamp
Shiftlevers	Shimano Sora Dual Control STI, 18-speed
Chain	KMC Z-9000
Cassette	SRAM PowerGlide 950, 9-speed, 11-26
Crankset	FSA Vero Compact, 50/34, 160mm (41) 170mm (48/51) 172.5mm (54/56) 175mm (58/61)
BB Set	Sealed cartridge, 68 x 110.5mm
Pedals	Touring platform, alloy cage/alloy body with toe clips
Brakeset	Tektro dual pivot calipers with Shimano Sora STI levers
Handlebar	Easton EA30 Road, 31.8mm, 380mm (41) 400mm (48/51) 420mm (54/56), 440mm (58/61)
Stem	Easton EA30 Road 6" x 75mm (41), 90mm (48/51) 105mm (54/56), 120mm (58/61)
Grips	Jamis cork tape
Seat Post	Easton EA30 Road, 300mm x 27.2mm with alloy clamp
Saddle	Selle San Marco Ischia
Sizes	48, 51, 54, 56, 58, 61cm
Color	Team Red
Weight	21.60 lbs

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
41 (650c)	15.08/383	19.29/490	71.5°	76°	14.76/375	36.42/925	1.57/40	10.51/268	3.54/90	26.38/670
48	16.42/417	20.27/515	71°	74°	16.34/415	38.50/978	1.97/50	10.51/267	3.94/100	27.87/708
51	18.11/460	20.67/525	71.5°	74°	16.34/415	38.78/985	1.97/50	10.51/267	4.72/120	29.13/740
54	18.78/477	21.18/538	72°	73.5°	16.34/415	38.78/985	1.77/45	10.51/267	5.51/140	29.88/759
56	19.60/498	21.85/555	72.5°	73°	16.34/415	38.86/987	1.69/43	10.51/267	6.30/160	30.67/779
58	20.23/514	22.44/570	72.5°	72.5°	16.34/415	39.41/1001	1.69/43	10.51/267	7.08/180	31.34/796
61	20.90/531	23.03/585	72.5°	72.5°	16.34/415	40.00/1016	1.69/43	10.51/267	7.87/200	32.01/813