

# 2009 JAMIS VENTURA SPORT FEMME

*Femme*

## UPGRADES FROM 2008

New 44cm Femme frame size

New FSA Tempo crank

Ritchey threadless headset



Gloss Black

## FEATURES/BENEFITS

The Ventura frame features Size Specific Tubing (SST): smaller frames are constructed with smaller diameter tubing to retain resiliency and ride quality, while larger frames are constructed using larger diameter tubing to retain stiffness for larger riders

Ventura Sport's frame is a competition inspired sloping top tube design featuring lightweight 7005 aluminum tubing and ride-tuned rear stays with a replaceable derailleur hanger

Our Femme version offers women's specific frame sizing & geometry and component selection, including anatomically adjusted top tube lengths & women's specific saddles, with handlebar, stem and crank lengths all dimensioned to optimally fit women for greater comfort & efficiency

The Jamis designed aluminum road fork features lightweight aluminum blades that handle precisely, with a chromoly steerer to assure strength and durability

A complete Shimano Sora/2200 16-speed drivetrain, including STI shifters, assures light, precise shifting throughout the entire gear range

Sport's wheelset features light-but-durable double-wall aluminum rims, smooth rolling Formula alloy hubs and stainless steel spokes trued precisely with even spoke tension to stay in true

FSA's compact chainring concept is revolutionary: a 34T inner chainring offers a 15% lower gear ratio than traditional 39T double ring'd road cranks, but the 50T outer loses only 6% off the top end compared to the 53T traditional outer. You get the hill climbing capability of a triple, yet weight less than a standard double

A sealed cartridge bottom bracket improves performance and reduces maintenance

Tektro's dual pivot brakes offer safe, secure braking and high quality forged alloy construction

Vittoria's Zaffiro 23c tires offer legendary, road-holding capability and superior ride quality

Our over-sized 31.8 bar & stem combination offers greater support & stiffness when sprinting out of the saddle

With 55mm of shim stack under the stem out of the box allowing for over 2" of stem height adjustability

## SPECIFICATIONS

Frame	Kinesis 7005 taper-gauge aluminum, SST tubing diameters, sloping top tube frame design, replaceable derailleur hanger
Fork	Alloy, straight blade Aero Road with cromoly steerer
Headset	Ritchey LB threadless Aheadset, 1 1/8
Wheels	Alex ID19 double-walled rims, 700c 32H with Formula hubs, 14g stainless steel spokes
Tires	Vittoria Zaffiro, 700 x 23c
Derailleurs	Shimano Sora rear & 2200 front, 31.8mm clamp
Shiftlevers	Shimano 2200 Dual Control STI, 16-speed
Chain	KMC Z-82
Cassette	SRAM PowerGlide 850, 8-speed, 12-26
Crankset	FSA Tempo Compact, 50/34, 165mm (44/48), 170mm (51/54)
BB Set	Sealed cartridge, 68 x 110.5mm
Pedals	Touring platform, alloy cage/alloy body with toe clips
Brakeset	Tektro dual pivot calipers with Shimano 2200 STI levers
Handlebar	Jamis Road, 31.8mm with anatomic bend, 380mm (44/48) 400mm (51/54)
Stem	Jamis Forged Road, 6" x 80mm (44/48), 100mm (51/54)
Grips	Jamis cork tape
Seat Post	Jamis alloy micro-adjust road, 300mm x 27.2mm with alloy clamp
Saddle	Jamis Road Sport Women's with SL top and satin steel rails
Sizes	44, 48, 51, 54cm
Color	Gloss Black
Weight	22.70 lbs

## GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
44 W	15.08/ <b>383</b>	19.49/ <b>495</b>	70.5°	76°	16.34/ <b>415</b>	38.74/ <b>984</b>	1.97/ <b>50</b>	10.71/ <b>272</b>	3.94/ <b>100</b>	27.79/ <b>706</b>
48 W	16.42/ <b>417</b>	19.88/ <b>505</b>	71°	75.5°	16.34/ <b>415</b>	38.94/ <b>989</b>	1.97/ <b>50</b>	10.71/ <b>272</b>	3.94/ <b>100</b>	28.50/ <b>724</b>
51 W	18.11/ <b>460</b>	20.27/ <b>515</b>	71.5°	75°	16.34/ <b>415</b>	38.90/ <b>988</b>	1.97/ <b>50</b>	10.71/ <b>272</b>	4.72/ <b>120</b>	29.76/ <b>756</b>
54 W	18.78/ <b>477</b>	20.87/ <b>530</b>	72°	74°	16.34/ <b>415</b>	38.70/ <b>983</b>	1.69/ <b>43</b>	10.71/ <b>272</b>	5.51/ <b>140</b>	30.47/ <b>774</b>